CENTRAL INTELLIGENCE AGENCY

INFORMATION REPORT

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorised person is prohibited by law.

SECRET/CONTROL - U.S. OFFICIALS ONLY

UBJECT	•	Radar Parts Production at the 9th	of May	DATE DISTR.	9 Au	9 August 1954	
		Factory in Brodce nad Sazavou		NO. OF PAGES	2	25X1	
ATE O	F INFO.			REQUIREMENT NO.	RD ~		
LACE ACQUIRED					KD.	25X1	
LACE	CGOIKED	This is UNEVALUATED		REFERENCES	04.		
		THIS IS SIVE VIZES/(TES			64	2338	
-		THE SOURCE EVALUATIONS IN THIS THE APPRAISAL OF CONTEN (FOR KEY SEE REV	T IS TENTAT				
1.	Radar 1 mm.t	magnets are cast from magnetic stee	approxi	mately 2½ kg. T	inum,		
	are ca	ast at the Metallurgical Works at Tj	mec nad	Sazavou.⊥			
2.	Plant,	magnet in the experiment a magnet in the experiment a magnet in the experiment a magnet it from the Metallurgical Works.	ind deve	lopment departm	ent at the (fnu)		
2.	Plant,	magnet in the experiment a state of the control of	and deve	lopment departm	(fnu)	9th of May 25X1	
	Plant, received instal consist larger smalle	magnet in the experiment a state of the control of	the mag	cher Eng. Dedekter Eng. Dedekt	n radar h coil ls were t. Two		
	Plant, received instal consist larger smalle	ast at the Metallurgical Works at Ty magnet in the experiment at CZavoda 9; Kvetne at Brodce nad Sazaved it from the Metallurgical Works. Lations. Five coils were to be worsting of steps of copper wire, 2 mm. in size and were to be placed in the coils followed and the smallest of	the mag	cher Eng. Dedekter Eng. Dedekt	n radar h coil ls were t. Two	25X1	
	Plant, received instal consistance smalle between	magnet in the experiment a (Zavoda 9, Kvetna) at Brodce nad Sazared it from the Metallurgical Works. Clations. Five coils were to be wounded in size and were to be placed in the procise followed and the smallest of the horseshoe ends. Comments: Comments:	the mag	lopment departm fter Eng. Dedek mets are used i me casting, eac Two of the coi er of the magne placed in the o	n radar h coil ls were t. Two pen part	25X1	
	Plant, receive instal consistance smalle between 1. Me Ty	magnet in the experiment a (Zavoda 9, Kvetna) at Brodce nad Sazared it from the Metallurgical Works. Clations. Five coils were to be worsting of steps of copper wire, 2 mm, in size and were to be placed in the croils followed and the smallest on the horseshoe ends. Comments:	the mag und on o thick. the cent one was	lopment departm fter Eng. Dedek mets are used i ne casting, eac Two of the coi er of the magne placed in the o	n radar h coil ls were t. Two pen part	25X1	
	Plant, receive instal consistance smalle between 1. Me Ty	nagnet in the experiment a (Zavoda 9; Kvetna) at Brodce nad Sazaved it from the Metallurgical Works. Lations. Five coils were to be worsting of steps of copper wire, 2 mm. in size and were to be placed in the coils followed and the smallest cent the horseshoe ends. Comments: Stallurgic Works (Metalurgicke zavomec nad Sazavou.	the mag und on o thick. the cent one was	lopment departm fter Eng. Dedek mets are used i ne casting, eac Two of the coi er of the magne placed in the o	n radar h coil ls were t. Two pen part	25X1 25X1 25X1 •	
	Plant, receive instal consistance smalle between 1. Me Ty	nagnet in the experiment a (Zavoda 9; Kvetna) at Brodce nad Sazaved it from the Metallurgical Works. Lations. Five coils were to be worsting of steps of copper wire, 2 mm. in size and were to be placed in the coils followed and the smallest cent the horseshoe ends. Comments: Stallurgic Works (Metalurgicke zavomec nad Sazavou.	the mag und on o thick. the cent one was	lopment departm fter Eng. Dedek mets are used i ne casting, eac Two of the coi er of the magne placed in the o	n radar h coil ls were t. Two pen part	25X1 25X1 25X1	
	Plant, receive instal consistance smalle between 1. Me Ty	nagnet in the experiment a (Zavoda 9; Kvetna) at Brodce nad Sazaved it from the Metallurgical Works. Lations. Five coils were to be worsting of steps of copper wire, 2 mm. in size and were to be placed in the coils followed and the smallest cent the horseshoe ends. Comments: Stallurgic Works (Metalurgicke zavomec nad Sazavou.	the mag und on o thick. the cent one was	lopment departm fter Eng. Dedek mets are used i ne casting, eac Two of the coi er of the magne placed in the o	n radar h coil ls were t. Two pen part	25X1 25X1 25X1 •	
	Plant, receive instal consistance smalle between 1. Me Ty	nagnet in the experiment a (Zavoda 9; Kvetna) at Brodce nad Sazaved it from the Metallurgical Works. Lations. Five coils were to be worsting of steps of copper wire, 2 mm. in size and were to be placed in the coils followed and the smallest cent the horseshoe ends. Comments: Stallurgic Works (Metalurgicke zavomec nad Sazavou.	the mag und on o thick. the cent one was	lopment departm fter Eng. Dedek mets are used i ne casting, eac Two of the coi er of the magne placed in the o	n radar h coil ls were t. Two pen part	25X1 25X1 25X1 • 25X1	
	Plant, receive instal consistance smalle between 1. Me Ty	nagnet in the experiment a (Zavoda 9; Kvetna) at Brodce nad Sazaved it from the Metallurgical Works. Lations. Five coils were to be worsting of steps of copper wire, 2 mm. in size and were to be placed in the coils followed and the smallest cent the horseshoe ends. Comments: Stallurgic Works (Metalurgicke zavomec nad Sazavou.	the mag ind on o thick. he cent one was	lopment department of the Eng. Dedek mets are used in the costing, each of the magner of the magner placed in the obtained Enterprise,	n radar h coil ls were t. Two pen part	25X1 25X1 25X1 • 25X1	

(NOTE: Washington distribution indicated by "X"; field ...tribution by "#".)


SECRET/CONTROL - U.S. OFFICIALS ONLY


- 2 -

25X1


RADAR MAGNET

All measurements in millimeters






COIL WOUND ON THE MAGNET



Coil cross-section



Not to Scale

SECRET/CONTROL - U.S. OFFICIALS ONLY